

C class

Product Information
GHC625SI

MODEL

GHC625IX

Energy efficiency classes of domestic range hoods (A-G)

C

Annual Energy Consumption - AEC hood (kWh/a)

51,3

Fluid Dynamic Efficiency classes for domestic range hoods (A-G)

E

Lighting Efficiency classes (A-G)

D

The Grease Filtering Efficiency classes (A-G)

E

Sound power level L WA - (dB)

65

Time increase factor - f

1,7

Fluid Dynamic Efficiency - FDE hood

8,5

Energy Efficiency Index - EEI hood

84,9

Measured air flow rate at best efficiency point - Q BEP (m³/h)

138,2

Measured air pressure at best efficiency point P BEP (Pa)

173,4

Measured electric power input at best efficiency point - W BEP (W)

78

Nominal power of the lighting system - W L (W)

4

Average illumination of the lighting system on the cooking surface - E middle (lx)

72

Lighting Efficiency LE hood - (lux/Watt)

18

Grease Filtering Efficiency GFE hood - (%)

78

Minimum airflow (Q min)

126m³/hMaximum air flow - Q max (m³/h)230m³/h

Airflow -boost (Q boost)

-

Minimum sound power level L WA - (dB)

45dB

Maximum sound power level L WA - (dB)

65dB

Sound power level-boost L WA - (dB)

-

Measured power consumption off mode P o (W)

0

Measured power consumption in standby mode - P s (W)

0

Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "